

**CERTIFICATE OF CONFORMITY****23 – НУРВСПСПБ – PL – 030 - 37**

Issued pursuant to Art. 14, par.1 and/or par.2 of Ordinance № RD-02-20-1 from 05.02.2015 on the terms and the conditions for the use of construction products in the construction works of the Republic of Bulgaria of the Ministry of Regional Development and Public Works for the construction product

**Manholes and inspection chambers from polypropylene (PP)**

Intended for non-pressure underground drainage and sewerage systems up to a maximum depth of 6 m from ground level to the invert of the manhole or inspection chamber and are intended to be used in pedestrian or vehicular traffic areas outside the building structure, with dimensions and evaluated characteristics in accordance with Annex № 1 to this Certificate

Released on the market by:

**“PIPELIFE BULGARIA“ EOOD**  
**3 Industrialna Street, Botevgrad, Bulgaria**

Produced by:

**PIPELIFE POLSKA S.A.**  
**4 Torfowa Str., Kartoszyno, 84-110 Krokowa, Poland**

This Certificate certifies that the product has been evaluated and conforms to the national requirements, defined in

**BDS EN 13598-2:2020/NA:2022**  
**BDS EN 13598-2:2020**

*and Annex № 2, point 25 to item 2 of Order № ПД-02-14-1329 from 03.12.2015 of the Minister of the Regional Development and Public Works, amended and supplemented by Order № ПД-02-14-252 from 10.03.2021*

The Certificate was issued for the first time on **17.02.2023** and remains valid until **16.02.2026**, provided that the producer ensures consistency of product characteristics and the conditions of production or production control have not been changed significantly.

**Place of issuance: Sofia**  
**Date: 17.02.2023****CEO:** BULAQUA STANDART  
**(Dipl. Ing. Alexander Marinchev)**

*This certificate includes 1 Annex of 1 page, which is an integral part of the same.*

**Annex №1**

**to Certificate of conformity № 23 – НУРВСПСРБ – PL – 030 – 37**

**issued on 17.02.2023 and valid until 16.02.2026**

**1. Range and dimensions**

Product	Nominal diameter, mm	Trademark	Technology of production
Inspection chamber	$200 \leq d_n \leq 400$	PRAKTO	Injection moulding
Manhole	$600 \leq d_n \leq 1200$	PRO	

**2. Evaluated characteristics in accordance with the national requirements**

Characteristic	Declaration requirement
Appearance	According to item 6.1 of BDS EN 13598-2
Colour	According to item 6.2 of BDS EN 13598-2
Geometrical characteristics	According to item 7 of BDS EN 13598-2
Ring stiffness of the riser	$\geq 2 \text{ kN/m}^2$ According to item 8, table 7 of BDS EN 13598-2
Impact resistance	No cracks or other damages impairing the function of the base
Manhole steps strength at vertical load 2kN	Deflection under load $\leq 10 \text{ mm}$ Remaining deflection $\leq 5 \text{ mm}$
Leak-tightness for base-riser connections	No leakage
Tightness of elastomeric ring sealing joints for base-pipe connections	No leakage

**Place of issuance: Sofia**  
**Date: 17.02.2023**

**CEO:** BULAQUA STANDART  
**(Dipl. Ing. Alexander Marinchev)**